

GNU Fortran Internals

For GCC version 16.0.0 (pre-release)

(GCC)

The gfortran team

Published by the Free Software Foundation
51 Franklin Street, Fifth Floor
Boston, MA 02110-1301, USA

Copyright © 2007-2025 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.3 or any later version published by the Free Software Foundation; with the Invariant Sections being “Funding Free Software”, the Front-Cover Texts being (a) (see below), and with the Back-Cover Texts being (b) (see below). A copy of the license is included in the section entitled “GNU Free Documentation License”.

(a) The FSF’s Front-Cover Text is:

A GNU Manual

(b) The FSF’s Back-Cover Text is:

You have freedom to copy and modify this GNU Manual, like GNU software. Copies published by the Free Software Foundation raise funds for GNU development.

Short Contents

1	Introduction.....	1
2	Code that Interacts with the User	3
3	Frontend Data Structures	5
4	Internals of Fortran 2003 OOP Features	11
5	Generating the intermediate language for later stages.....	13
6	The LibGFortran Runtime Library	15
	GNU Free Documentation License.....	17
	Index	25

Index.....	25
-------------------	-----------

1 Introduction

This manual documents the internals of **gfortran**, the GNU Fortran compiler.

Warning: This document, and the compiler it describes, are still under development. While efforts are made to keep it up-to-date, it might not accurately reflect the status of the most recent GNU Fortran compiler.

At present, this manual is very much a work in progress, containing miscellaneous notes about the internals of the compiler. It is hoped that at some point in the future it will become a reasonably complete guide; in the interim, GNU Fortran developers are strongly encouraged to contribute to it as a way of keeping notes while working on the compiler.

not an error existed. To check the state of the buffer without changing its state or reporting the errors, the `gfc_error_flag_test` function can be used. The `gfc_clear_error` function will clear out any errors in the buffer, without reporting them. The `gfc_warning_check` and `gfc_clear_warning` functions provide equivalent functionality for the warning buffer.

Only one error and one warning can be in the buffers at a time, and buffering another will overwrite the existing one. In cases where one may wish to work on a smaller piece of source code without disturbing an existing error state, the `gfc_push_error`, `gfc_pop_error`, and `gfc_free_error` mechanism exists to implement a stack for the error buffer.

For cases where an error or warning should be reported immediately rather than buffered, the `gfc_error_now` and `gfc_warning_now` functions can be used. Normally, the compiler will continue attempting to parse the program after an error has occurred, but if this is not appropriate, the `gfc_fatal_error` function should be used instead. For errors that are always the result of a bug somewhere in the compiler, the `gfc_internal_error` function should be used.

The syntax for the strings used to produce the error/warning message in the various error and warning functions is similar to the `printf` syntax, with `'%'`-escapes to insert variable values. The details, and the allowable codes, are documented in the `error_print` function in `error.cc`.

3.2.7 Constant Substring References

`EXPR_SUBSTRING` is a special type of expression that encodes a substring reference of a constant string, as in the following code snippet:

```
x = "abcde"(1:2)
```

In this case, `value.character` contains the full string's data as if it was a string constant, but the `ref` member is also set and points to a substring reference as described in the subsection above.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C)  year  your name.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.3
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover
Texts. A copy of the license is included in the section entitled ``GNU
Free Documentation License''.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with
the Front-Cover Texts being list, and with the Back-Cover Texts
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

D

data structures..... 5

F

FDL, GNU Free Documentation License..... 17

G

gfc_code 5

gfc_expr 7

S

statement chaining..... 5

struct gfc_code..... 5

struct gfc_expr..... 7